


INCLUDED ACCESSORIES



CASING RELIEF VALVE		
PUMP FLOW (GPM)	VALVE INLET	"C" DIMENSION
50 - 2500	1/2"	7.438 [190]
3000 - 5000	3/4"	7.438 [190]

FLOAT OPERATED AIR RELEASE VALVE		
SYSTEM PRESSURE (PRESSURE)	HEIGHT	WIDTH
UP TO 175 PSI	12.438 [316]	7.500 [191]
OVER 175 PSI	12.438 [316]	7.500 [191]

NOTES:

- ALL DIMENSIONS ARE IN INCHES [MM] AND MAY VARY ± 0.375 INCHES.
- REFER TO AMERIFLO INSTALLATION, OPERATION AND MAINTENANCE MANUAL FOR PROPER PUMP INSTALLATION.
- ACCESSORIES ARE SHIPPED LOOSE FOR FIELD INSTALLATION.
- CASING RELIEF VALVE IS FURNISHED ON ELECTRIC MOTOR DRIVEN PUMPS ONLY.
- DISCHARGE GAUGE IS 0 - 300 PSI FOR PUMPS WITH RATED DISCHARGE PRESSURE UP TO 150 PSI OR 0 - 600 PSI FOR PUMPS WITH RATED PRESSURE OVER 150 PSI.
- THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION UNLESS CERTIFIED BY AMERIFLO.