

SERIES 4820

BOWL

ASSEMBLY

MIXED FLOW

Bowls: 16” to 72” Diameter
Flows: To 220,000 GPM
Heads: To 50 Feet
Temp: To 250°F

Services:

Cooling Water
Raw Water Intake
Sea Water
Industrial Process
Condenser Circulating
Irrigation & Drainage
Municipal Water Supply

BOWL ASSEMBLY

- Supplied standard in ASTM A48 cast iron
- Heavy wall thickness for corrosion allowance
- Includes investment cast, 304 stainless steel, Axial Flow impellers
- 304 stainless steel shaft sleeves completely protect the shaft from wear and corrosion
- Mixed Flow impeller design allows for broad band, high efficiency performance
- Impellers are machined and dynamically balanced prior to assembly
- 4340 quenched and tempered high chrome steel shaft is stronger than standard carbon steel and has superior corrosion resistance
- Keyed impeller construction for high horsepower applications
- Bronze bowl bearings
- Flanged construction with jackscrew threads for easy assembly and disassembly
- Alternate metallurgy options available upon request

LINESHAFT COUPLINGS

- Smaller HP models feature threaded lineshaft couplings while larger sizes have keyed lineshaft couplings standard
- Alternate metallurgy options available upon request

BOWL SHAFT

- Oversized, 4340 quenched and tempered high chrome steel shaft is stronger than standard carbon steel and has superior corrosion resistance
- All impellers and bowl shaft sleeves are keyed to lock parts to the shaft assembly
- Unique shaft sleeve design with bowl shaft locknut and lockwasher does not require axial key at each impeller location

STRAINER

- Supplied standard in 304 stainless steel construction
- Protects the bowl assembly from large solids that may be present in the pumped fluid
- Optional vortex suppressor available upon request
- Alternate metallurgy options available upon request